






SERIE CREA

Porcelánicos Esmaltados / Glazed Porcelain-Characterísticas Técnicas / Technical Specifications

CARACTERÍSTICAS TÉCNICAS TECHNICAL DATA		NORMA STANDARD	VALORES PREVISTO-INTERNATIONAL STANDARES EN 14411 / ISO 13006-G	VALOR MEDIO NOKER NOKER AVERAGE VALUE	
	Water Absorption	ISO 10545-3	Averages 0.5% individual	Conform to standard	
	Breaking Strength	ISO 10545-4	>1300N	Conform to standard	
	Modulus of rupture	ISO 10545-4	≥35 N/mm ²	Conform to standard	
	Slip-resistance	DIN 51130 R	From R9 to R13	Conform to standard	
		ASTM C 1028	≥0.5	Conform to standard	
	Abrasion resistance	ISO 10545-7	Class PEI	Conform to standard	
	Length and width		±0.5% MAX	Pass	
	Side straightness		±0.5% MAX	Pass	
	Dimension	Rectangularity	ISO 10545-2	±0.6% MAX	Pass
		Centre curvature		±0.5% MAX	Pass
		Edge curvature		±0.5% MAX	Pass
	Thermal expansion coefficient	ISO 10545-9	Test method available	Resistant	
	Frost resistance	ISO 10545-12	Required	Resistant	
	Resistance to household chemical and swimming pool water	ISO 10545-13	Minimum class B	Guaranteed GA	
	Stain resistance	ISO 10545-14	≥Class 2	Class 5	
	Determination of the crazing resistance	ISO 10545-12	Required	Resistant	