












# SERIE HABANA

Porcelánicos Esmaltados / Glazed Porcelain-Characterísticas Técnicas / Technical Specifications

CARACTERÍSTICAS TÉCNICAS TECHNICAL DATA	NORMA STANDARD	VALORES PREVISTO-INTERNATIONAL STANDARES EN 14411 / ISO 13006-G	VALOR MEDIO NOKER NOKER AVERAGE VALUE	
	Water Absorption	ISO 10545-3	Average $\leq 0,5\%$ individual	Conform to standard
	Breaking Strength	ISO 10545-4	>1300N	Conform to standard
	Modulus of rupture	ISO 10545-4	$\geq 35$ N/mm <sup>2</sup>	Conform to standard
	Slip-resistance	DIN 51130 R	From R9 to R13	Conform to standard
	Abrasion resistance	ASTM C 1028	$\geq 0,5$	Conform to standard
	Length and width		$\pm 0,5\%$ MAX	Pass
	Side straightness		$\pm 0,5\%$ MAX	Pass
	Dimension Rectangularity	ISO 10545-2	$\pm 0,6\%$ MAX	Pass
	Centre curvature		$\pm 0,5\%$ MAX	Pass
	Edge curvature		$\pm 0,5\%$ MAX	Pass
	Thermal expansion coefficient	ISO 10545-9	Test method available	Resistant
	Frost resistance	ISO 10545-12	Required	Resistant
	Resistance to household chemical and swimming pool water	ISO 10545-13	Minimum class B	Guaranteed GA
	Stain resistance	ISO 10545-14	$\geq$ Class 2	Class 5
	Determination of the crazing resistance	ISO 10545-12	Required	Resistant